



- `TABLET` 8.4

### Tablet

- `TABLET`

### Tablet

#### Tablet

```
production_de ↙
production_es ↗→ production_all84
production_it ↘
```

#### Tablet

- `production_de` `PRODUCTION`
- `production_es` `PRODUCTION`
- `production_it` `PRODUCTION`
- `production_all84`
  - `PRODUCTION_DE`
  - `PRODUCTION_ES`
  - `PRODUCTION_IT`

#### Tablet

### Tablet

#### Tablet

- `server-id`



```
super_read_only = ON
```

```
skip_replica_start=ON [REDACTED]
```

```
[REDACTED]
```

```
[REDACTED]
```

```
CREATE USER 'repl'@'10.68.68.%' IDENTIFIED BY 'Repl84Geo2026x';  
GRANT REPLICATION SLAVE, REPLICATION CLIENT ON *.* TO 'repl'@'10.68.68.%';
```

```
REPLICATION SLAVE [REDACTED] MySQL [REDACTED] 8.4 [REDACTED]
```

```
[REDACTED]
```

```
[REDACTED]
```

```
[REDACTED]
```

```
mysqldump --single-transaction --set-gtid-purged=OFF PRODUCTION > PRODUCTION_de.sql  
mysqldump --single-transaction --set-gtid-purged=OFF PRODUCTION > PRODUCTION_es.sql  
mysqldump --single-transaction --set-gtid-purged=OFF PRODUCTION > PRODUCTION_it.sql
```

```
[REDACTED]
```

```
CREATE DATABASE PRODUCTION_DE;  
CREATE DATABASE PRODUCTION_ES;  
CREATE DATABASE PRODUCTION_IT;
```

```
[REDACTED]
```

## [[ binlog ]]

```
[REDACTED] GTID [REDACTED]
```

- binlog [REDACTED]
- [REDACTED]

```
[REDACTED]
```

```
SHOW BINARY LOG STATUS;
```

```
SOURCE_LOG_FILE SOURCE_LOG_POS
```

```
MySQL 8.4 CHANGE REPLICATION SOURCE TO ... FOR CHANNEL
```

```
CHANGE REPLICATION SOURCE TO
SOURCE_HOST='10.68.68.186',
SOURCE_PORT=3306,
SOURCE_USER='repl',
SOURCE_PASSWORD='Repl84Geo2026x',
SOURCE_LOG_FILE='mysql-bin.000001',
SOURCE_LOG_POS=158,
SOURCE_AUTO_POSITION=0,
GET_SOURCE_PUBLIC_KEY=1
FOR CHANNEL 'production_de';
```

- production\_es
- production\_it

```
PRODUCTION
```

```
CHANGE REPLICATION FILTER
REPLICATE_REWRITE_DB=((PRODUCTION,PRODUCTION_DE))
FOR CHANNEL 'production_de';
```

```
CHANGE REPLICATION FILTER
REPLICATE_REWRITE_DB=((PRODUCTION,PRODUCTION_ES))
FOR CHANNEL 'production_es';
```

```
CHANGE REPLICATION FILTER
  REPLICATE_REWRITE_DB=((PRODUCTION,PRODUCTION_IT))
FOR CHANNEL 'production_it';
```

□□□□

- `CHANGE REPLICATION FILTER ... FOR CHANNEL` □□□□□□□□□□
- `MySQL` □□□□

□□□□

```
START REPLICA FOR CHANNEL 'production_de';
START REPLICA FOR CHANNEL 'production_es';
START REPLICA FOR CHANNEL 'production_it';
```

□□□□□□□□□□□□

```
SET GLOBAL read_only = ON;
SET GLOBAL super_read_only = ON;
```

□□

□□□□□□

```
SHOW REPLICA STATUS FOR CHANNEL 'production_de'\G
SHOW REPLICA STATUS FOR CHANNEL 'production_es'\G
SHOW REPLICA STATUS FOR CHANNEL 'production_it'\G
```

□□□□

- `Replica_IO_Running`: Yes
- `Replica_SQL_Running`: Yes
- `Seconds_Behind_Source`: 0 □□
- `Replicate_Rewrite_DB` □□□□

□□□□



- 1
- 2

3

- 4
- 5
- 6

7

8 MySQL 8.4 9

10

1. 11
2. server-id 12
3. 13
4. 14
5. 15
6. 16

17 REPLICATE REWRITE DB 18

19

- MySQL 8.4 — 20
- 21
- 22
- 23
- CHANGE REPLICATION SOURCE TO